

**Mobile Tank Cleaning and Fuel Restoration Systems** clean tanks while reconditioning, stabilizing and decontaminating diesel, biofuels, light oils and hydraulic fluids. MTC systems remove water, sediment and sludge that naturally form and accumulate in tanks. They are compact, heavy-duty, multi-stage industrial systems for long-term reliable service. MTC systems clean tanks and restore fuel to its "Clear & Bright" pristine condition without the need for anyone to enter the tank.



### Mobile Tank Cleaning Systems feature:

- Multi-Stage Cleaning
- Minimal Consumables Used
- Low Operating Costs
- Compact Industrial Design
- Negligible Fuel Loss
- No Tank Entry Needed

### AXI's MTC Systems offer Three Stages of Fuel Conditioning

- **Stage 1:** The separator/coalescer removes water and particulate that clog filters and harm injectors.
- **Stage 2:** The ALGAE-X<sup>®</sup> Fuel Conditioner reconditions and stabilizes the fuel, reversing the process of fuel deterioration and buildup of tank sludge.
- **Stage 3:** The industrial type water block fine filter removes emulsified water and very fine solids down to 3 microns.

MTC Systems are built with industrial quality components mounted on a heavyduty aluminum cart. A clear suction hose and optional rotor sight glass show fuel flow and clarity. The large drip tray is designed to prevent spillage. Fuel can be polished without using any consumables by connecting the discharge hose to the quick disconnect bypassing the filter. An optional Digital Flow Meter measures the volume of liquid processed.

# MTC 3000 SPECIFICATIONS

Flow Rate	1560 GPH
Separator	Maintenance Free Centrifugal Water Separator/Coalescer
Spin-on Final Filter	1, 3, 10 or 25 μ Fine Filter 3 or 10 μ Water Block
Fuel Conditioner	LG-X 3000
Pump	Self priming rotary vane pump with integrated bypass valve & strainer
Power	115V 60Hz 20A or 230V 50Hz 20A
Ports	1" Quick Disconnect
Clear Suction Hose	1-1/2", 25 ft
Discharge Hose	1-1/4" , 25 ft
Dimensions	48" x 22.5" x 25" (122 x 57 x 63 cm)
Weight	200 lbs
Not for use with fluids that have a flash point below 100°F.	

## MTC 3000 Principal Components

The **principal components** are a self-priming vane pump with integrated bypass valve and strainer, maintenance free centrifugal water separator/coalescer, spin-on fine filter and water block filters, an ALGAE-X Fuel Conditioner and clear suction hoses.

### MTC Options

AXI customized Pre-Filter Assemblies have a large contaminant holding capacity to save time and accelerate the cleaning of tanks with large amounts of sludge, rust, scale and sediments.

AXI Spill Containment Berms protect the environment and are industrial quality, easy to use and fold up for storage and transportation.

AFC-705 Fuel Catalyst is a broad-spectrum fuel additive concentrate that enhances the breakdown and removal of sludge, slime and bio-fouling from tank walls and baffles.



+1-239-690-9589 1-877-425-4239 Toll Free www.AXIFuelConditioning.com Wherever fuel is being used or stored